

SPECIFICATIONS

製品名	PURE+	VISION	SPOT	
製品 No	MHS-PH3000	MHS-VT3200	MHS-SP1600	MHS-SP2800
サイズ	1044 x 166 x 87 mm	1660 x 184 x 87 mm	670 x 184 x 78 mm	884 x 184 x 78 mm
重量	6.5kg	11.0kg	4.0kg	5.0kg
電圧	200 VAC – 50/60 Hz		100 VAC – 50/60 Hz	200 VAC – 50/60 Hz
消費電力	3000 W	3200W	1600W	2800W
電流	15 A	16A	16A	14A
ケーブル	1.1 m / 4 x 2.0 mm ²	1.1 m / 3 x 2.0 mm ²	1.1 m / 3 x 2.0 mm ²	
表面温度	max. 350° C (PURE+ with glass) max. 450° C (PURE+ with grid)	300° C	400° C	
筐体温度	max. 120° C	max. 130° C	max. 150° C	
フィラメント温度	1100-1300° C	1200-1300° C	1200-1300° C	
色温度	1550-1650 K	1550-1650 K	1550-1650 K	
最大出力	ca. 20–30 Sec. (PURE+ with glass) ca. 15–20 Sec. (PURE+ with grid)	ca. 30–60 Sec.	ca. 15 Sec.	
可視光	< 300–400 Lumen (PURE+ with glass) < 600 Lumen (PURE+ with grid)	< 300 Lumen	< 600 Lumen	
推奨設置高さ	min. 1.8 m / max. 2.5 m		min. 1.8 m / max. 3 m	
IP安全等級	IP 65 (PURE+ with glass) IP 25 (PURE+ with grid)	IP 44 (well covered or with optional weather shield)	IP 24 (well covered or with optional weather shield)	
価格	320,000 円	350,000 円	180,000 円	220,000 円

※ 表示価格は全て税抜です。 ※ 一部日本では未販売の商品がございます。詳しくはお問い合わせください。